

Analogiset CCTV-kamerat

CA-42-49/IRD-4

83,00 €



Sensor:	1/3" Sony CCD
Lens:	4 - 9 mm
View angle:	72° - 31°
Resolution:	420 TVL
Video output:	1 Vpp / 75Ω
Number of IR LEDs:	36
Range of IR illumination:	30 m
S/N ratio:	> 48 dB
Weight (with bracket):	810 g
Dimensions (with bracket):	220 x 120 x 83 mm
Operation temp.:	from -10°C to +50°C
Power supply:	DC 12V / 440mA
Video / power connectors:	BNC socket / 2.1/5.5mm socket

Tarkennus ja Zoom nupit kameran alla.

CA70-2810/IRD-4C

115,00 €



Sensor:	1/3" Sony EXview HAD CCD II
Image processor:	DSP Sony Effio
Lens:	2.8 - 10 mm
View angle:	81° - 27°
Resolution:	700 TVL
Video output:	1 Vpp / 75Ω
Number of IR LEDs:	42
Range of IR illumination:	40 m
Electronic shutter:	1/50 - 1/100000 s
OSD menu:	Yes, external controller on the cable
Main features:	<ul style="list-style-type: none">• Sony EFFIO Image Processor• NR (DNR) - Noise Reduction• BLC - BackLight Compensation• Motion Detection - configurable• Privacy Zones - configurable (max. 4 zones)• Sharpness - sharper image outlines
Weight (with bracket):	850 g
Dimensions (with bracket):	220 x 120 x 83 mm
Operation temp.:	from -10°C to +50°C
Power supply:	DC 12V / 480mA
Video / power connectors:	BNC socket / 2.1/5.5mm socket

Tarkennus ja Zoom nupit kameran alla.

CC-5336X

148,00 €



36x optinen moottoroitu zoom ja autofokus. Ohjaus RS485-ohjaimella tai nupeilla kameran takana.

Sensor:	1/4" SONY Super HAD CCD
Lens:	MOTOZOOM (3.9 - 140.4 mm)
Min. illumination:	0.1 Lux
Resolution:	500 TVL
Video output:	1 Vp-p / 75Ω
View angle:	49.4° - 1.4°
Optical zoom:	x36
OSD menu:	Yes
AUTOFOCUS:	Yes
RS-485 interface:	Yes (PELCO-D, 2400kbps)
Operation temp.:	from -10°C to +50°C
Weight:	430 g
Dimensions:	108 x 68 x 65 mm
Power supply:	DC 12V / 350 mA