



H218W

HD 720P 1.0 megapikseli kamera IP66

Datalehti

Specifications		
ITEMS		H218W
Image Sensor	Image Sensor	1 / 3" 1.0 megapixel progressive CMOS sensor,
	Display Resolution	1280 x 720 Pixels(1.0Megapixel 720P)
	Lens	f: 8mm, F:1.2 (IR Lens) 12mm optional
	Mini. Illumination	IR Light on, 0 Lux
Lens	Lens Type	Glass Lens
	IR-Cut	IR-Cut filter built-in, true color with IR lens
	Viewing Angle	45 Degree
Audio	Input	1 channel MIC input
	Output	1 channel Linear output
	Audio Compression	G.711/G.726
Video	Image Compression	H.264 Main Profile 3.0/ MJPEG Dual Stream
	Image Frame Rate	1~30fps(1280x720),1~30fps(320x240)
	Resolution	1280x720,960x540
	Flip Mirror Images	Vertical / Horizontal
	Light Frequency	50Hz, 60Hz
	Video Parameters	Brightness, Contrast
Communication	Ethernet	One 10/100Mbps RJ-45
	Supported Protocol	HTTP,FTP,TCP/IP,UDP,SMTP,DHCP,PPPoE,DDNS,UPnP,GPRS
	Wireless Standard	IEEE 802.11b/g/n
	Data Rate	802.11g: 54Mbps(Max.), 802.11n: 150Mbps(Max.)
	Wireless Security	WEP&WPA&WPA2 Encryption
Physical	Infrared Light	36 Φ8 IR LEDs,Night visibility up to 40metres
	Dimension	220m(L)*112mm(W)*106mm(H)
	Gross Weight	1.7kg (Color Box Size:290x180x135mm)
	Net Weight	1.5Kg (accessories included)
Power	Power Supply	DC 12V/1A (EU,US,AU adapter optional)
	Power Consumption	12 Watts (Max.)
Environment	Operate Temper.	-20 ~ 60 °C (-4 ~ 140 °F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temper.	-10°C ~ 60° (14°F ~ 140°F)
	Storage Humidity	0% ~ 90% non-condensing
PC Requirements	CPU	2.0GHZ or above (suggested 3.0GHZ)
	Memory Size	512MB or above (suggested 1.0GHZ)
	Display Card	64M or above
	Supported OS	Microsoft Windows 2000/XP/Vista
	Browser	IE 7, IE8, Firefox, Safari or other standard browsers
Certification	CE,FCC	
Warranty	Limited 1-year warranty	