

WANSCAM HW0022 1080p (2 MPix) ulkokamera



Pääominaisuudet:

1. H.264, DC 5V2A. 1Megapixel. 1080P.
2. 6 Jumbo-IR leds, IR distance 20M. Lens 3.6mm
3. Wi-Fi/802.11/b/g/n, Free PC CMS Software.
4. Motion detection, email alert, FTP upload
5. Support Video Mask and Special Area Dection
6. 12 languages, Firefox, Safari, Google, IE browser
7. Built-in IR Cut, No Color Cast.
8. P2P, PNP: Plug&play, Support QR code scanning to view on Iphone and android Mobiles
9. Support standard **Onvif protocol**
10. Mobiilituki (E-View7) Android ja iOS
11. Koko 148 x 60 mm ja paino 289 g.
12. Alumiinikotelo, valkoinen
- 11: Kamerassa on n. 40 cm pitkä häntäkaapeli, jonka päässä data- ja virtaliittimet + reset-nuppi
- 12: Max. 128GB TF-muistikortti (Micro SD)

Huomaa: Kameran antenniliitin tulee suojata sateelta, katso erillinen ohje.

Testattu toimivaksi:

- Chrome + IE-Tab, IE
- Netcam Watcher Pro (Snapshot)
- iSpy

System	System Security	Supports three-level account, password, user authority management.
	OS	Embedded Linux OS
	Processor	Hi3516C
	P2P (Free)	No need to preset camera, Offer free P2P, Plug&play, Support QR code scanning to view
	Onvif Protocol	Support ONVIF Protocol
	Multi-device function	Support 12 language remote surveillance, record, alarm, wifi setting etc.
	PC client	Support remote multi-devices monitor, record, alarm etc; Support Windows and Mac OS
	Cell Phone View	Self R&D APP, Support iPhone,Android smart phone
	TF Card Record	Support max 128GB
Lens	Lens Type	3.6MM
	IR-CUT	Build-in IR CUT, no color cast,auto switch when IR on
Video	Image Compression	H.264/MJPEG
	Sensor	1/2.7" Progressive Scan 2MP CMOS
	Video Parameters	Brightness, Contrast,Saturation,Exposure,sharpness can be adjusted
	Image Frame Rate	50Hz:25fps/60HZ:30fps (1920×1080)
	First Stream	1080P(1920×1080), 960P (1280×960) ,720P (1280×720)
	Second Stream	VGA-(640×352),(320×176)
	Third Stream	(320×176)
Night Vision	Night Visibility	8 Led lights,night vision up to 15 meters
	Lux	IR ON 0 LUX
Alarm	Motion Detect	Support 4 Independent detection areas(Sensitivity can be adjustd 1-100)
	Alarm Action	Support Email Photo Alert,Snapshot and Record uploaded to FTP
Network	Ethernet Interface	One 10/100Mbps RJ-45
	Supported Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP etc.
	Online Visitor	Support Max 6 visitors at the same time (First Stream:3 visitors;Second Stream:3 visitors)
	IP Mode	Dynamic IP address, static IP address (DHCP)
	Online Visitor	Support Microsoft Win XP/Win7/Win8/ win10/Mac OS.
	Browser	Support Internet Explorer 8.0-11.0, FireFox,Google Browser
	One key setting Function	Support one key setting function connect WIFI
	Wireless Standard	WIFI, 802.11b/g/n
Others	OSD	Support the OSD name, date and time info superposition (Open/Off)
	Product Type	Outdoor Use
	Power	DC5V/2A
	Working Temperature	-10~50 °C
	Working Humidity	95% RH
	Size	Item: 148 x 60mm (HxW); Packaging: 175 x78 x95 mm (LxWxH)
	Weight	N.W.: 289g G.W.: 461g (Note:Actual Weight Final)