

C76-2812

119,00 €



| | |
|----------------------------|--|
| Sensor: | 1/3" Sony EXview HAD CCD II |
| Image processor: | DSP Sony Effio-E |
| Lens: | 2.8 - 12 mm |
| View angle: | 81° - 27° |
| Resolution: | 700 TVL |
| Video output: | 1 Vpp / 75Ω |
| Number of IR LEDs: | 72 |
| Range of IR illumination: | 60 m |
| Electronic shutter: | 1/50 - 1/100000 s |
| OSD menu: | Yes, external controller on the cable |
| Main features: | <ul style="list-style-type: none">• Sony EFFIO Image Processor• 2-DNR - Noise Reduction• BLC - BackLight Compensation• Motion Detection - configurable• Privacy Zones - configurable (max. 4 zones)• Sharpness - sharper image outlines |
| Weight (with bracket): | 900 g |
| Dimensions (with bracket): | 300 x 100 x 105 mm |
| Operation temp.: | from -10°C to +50°C |
| Power supply: | DC 12V / 660mA |
| Video / power connectors: | BNC socket / 2.1/5.5mm socket |

Tarkennus ja Zoom nupit kameran alla.

CC-6527XEF

148,00 €



27x optinen moottoroitu zoom ja autofokus. Ohjaus RS485-ohjaimella tai nupeilla kameran takana.

| | |
|--------------------------|---|
| Sensor: | 1/4 " Sony CCD |
| Digital Image Processor: | — |
| Resolution: | 650 TVL |
| Lens: | 3.9 ... 105.3 mm (manufacturer data) |
| View angle: | 50 ° ... 2 ° (manufacturer data) |
| Optical zoom: | x 27 (manufacturer data) |
| Min. illumination: | 0.5 Lux |
| Video output: | 1 Vpp / 75 Ω |
| PTZ control: | RS-485 |
| Protocols: | Pelco-D |
| Main features: | <input type="checkbox"/> Very fast AutoFocus <input type="checkbox"/> AWB - Auto White Balance |
| OSD menu: | ✓ |
| Power supply: | 12 V DC / 290 mA |
| Operation temp: | -10 °C ... 50 °C |
| Weight: | 0.31 kg |

| | |
|-------------|------------------|
| Dimensions: | 104 x 60 x 60 mm |
|-------------|------------------|

