

WANSCAM HW0043 720p (1 MPix) ulkokamera



Pääominaisuudet:

1. H.264, DC 5V2A. 1Megapixel. 720P.
2. 13 IR leds, IR distance 10M. Lens 3.6mm
3. Wi-Fi/802.11/b/g/n ,Free PC CMS Software.
4. Motion detection, email alert, FTP upload
- 5.Support Video Mask and Special Area Dection
6. 12 languages, Firefox, Google,IE browser
7. Built-in IR Cut,No Color Cast.
8. P2P, PNP: Plug&play, Support QR code scanning to view on Iphone and android Mobiles
- 9.Support standard **Onvif protocol**
10. Mobiilituki (E-View7) Android ja iOS
11. Koko 17 x 5.2 x 6.9 cm ja paino 270 g.
12. Alumiinikotelo, valkoinen
- 11: Kamerassa on n. 40 cm pitkä häntäkaapeli, jonka päässä data- ja virtaliittimet + reset-nuppi

Huomaa: Kameran antenniliitin tulee suojata sateelta, katso erillinen ohje.

Testattu toimivaksi:

- Chrome
- FLEX NVR
- iSpy



Model: HW0043

System	System Security	Support three-level account,password, user authority management
	Operation System	Embedded Linux
	Micro-processor	HiSilicon 3518E
	P2P	No need to preset camera,plug and play, offer free P2P ID, support QR code scanning to view, easy setup
	ONVIF Protocol	Support ONVIF protocol
	PC Browser View	Support 12 languages, remote monitor, recording, alarm, WLAN parameters settings
	PC Client Software	Support remote multi-devices monitor, record, alarm etc
	Mobile View	Self-developed mobile app, available in App Store and Google Play
	TF Card Recording	NO
Lens	Lens Type	Glass Lens Standard: 3.6mm
	IR-CUT	Advanced IR-CUT technology, no color cast indoor and outdoor, auto switch when IR on
Video	Image Compression	H.264/MJPEG
	Cmos Sensor	1/4 inch 1MP progressive CMOS sensor
	Video Parameters	Brightness, contrast, saturability, sensitometry, acutance all adjustable
	Image Frame Rate	50Hz:25fps/60HZ:30fps (1280×720)
	Video Stream	First Stream: 720P (1280×720), (640×352),selectable Second Stream: VGA (640×352), (320×176),selectable
Audio	Audio Compression	None
	Audio Input	None
	Audio Output	None
Night Vision	Night Vision	13 leds;Night visibility up to 10 meters
	Minimum Illumination	0 Lux
PT	Preset	None
	Rotation Angle	None
	Rotation Speed	None
Alarm	Motion Detection	4 independent detecting areas, sensitivity(1-100) adjustable
	Alarm Action	Sending images to email;Uploading photos to FTP server
Network	Ethernet	One 10/100Mbps RJ-45
	Network Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP, etc
	Online Visitors	Support maximum 6 online visitors(First Stream:3 users, Second Stream:3 users)
	IP Mode	Static IP address,dynamic IP address(DHCP)
	System	Support Microsoft Win XP/Win7/Win8/win10.
	Browser	Support Internet Explorer 8-11,FireFox,Google Browser, etc
	One key Setting	Support One key Setting function